

Model:FIM-25K



Equipment features

- Internally-scraping ice skate can help reduce energy consumption and prevent leakage of refrigerant
- Stainless steel materials, advanced processing equipment and heat treatment ensure the best heat transfer efficiency
- The design of large water receiving plate can prevent water leaking at the bottom of drum
- Photoelectric switch is directly installed in the bottom of evaporator
- Direct liquid feeding and dry evaporation —— simple, safe and reliable control.
- Integrated modular equipment installation is convenient for maintenance.

Parameters

Subject		Unit	Technical parameter
Power supply		Voltage/Phase/Frequency	380V/3P/50Hz
Refrigerant			R22 or R404A
Temperature	Ambient temperature	℃	35
	Waterinlet temperature	℃	20
Operating power	Total running power	Kw	9.56
	Operating power of reducer	Kw	0.37
	Operating power of cold water pump	Kw	0.03
Capacity/stock	Capacity		2500
	Capacity of ice bin	Kg	1100
Compressor	Manufacturer		Maneurop
	Refrigeration capacity	Kw	14.45
	Operating power	Kw	8.26
	Compressor COP/EER	Kw/kw	1.75
	Horse power	Hp	12
Condenser	Fan power	Kw	0.45×2sets
	Cooling way		Air cooling
Dimension	Size of ice maker	(L×W×H)(mm)	1560×1200×1150
	Size of ice bin	(L×W×H)(mm)	1600×1400×950
	Size of water feeding pipe		1/2"
Weight of unit	Operating weight of flake ice maker	Kg	550
	Operating weight of ice bin	Kg	1200
Water supply pressure requirement		Bar	1